



Oil Types of the Norwest Basin of Argentina



L Ale Ruiz^{1*}, J Lezama¹, A Riveros Zapata² and JP Gutierrez³

¹Faculty of Engineering, National University of Salta, Argentina

²Faculty of Engineering, INBEMI, National University of Salta, Argentina

³Technological Institute of Buenos Aires- ITBA, CONICET, Argentina

*Corresponding author : L Ale Ruiz, Faculty of Engineering, Research Council, National University of Salta, Argentina, Email: laleruiz@unsa.edu.ar

Submission: 📅 April 04, 2018; Published: 📅 April 17, 2018

Introduction

Prior to producing a hydrocarbon deposit, performing a PVT study is necessary so that, based on the results of the studies, the various parameters and methodologies that will be developed to produce the deposit are determined. The PVT study is absolutely necessary in order to design the production facilities; in parallel, with this information the POES (Original Petroleum In Site) of the oilfield, the productive life of the deposit and the optimal production schemes are determined, in addition to evaluate methods of improved recovery of hydrocarbons and others properties that predict the behavior of the wells as they are exploited.

One part of the PVT study, the compositional one, is of great importance in the engineering of oilfields, since it helps to characterize the oilfield type and the volumetric conditions in which the oil is found, through the analysis of its behavior (volumetric and compositional), in order to establish the best strategy of exploitation and separation on the surface. This study involves a set of laboratory analysis of the samples, one of which is the differential expansion of the fluid sample to determine the Bo (volumetric factor of oil formation) and RPG or GOR (gas-oil relationship), this last ones are essential to classify oil in situ, in addition to the API gravity.

One of the most important indicators is the GOR, which is the amount of associated gas separated during production, by obtaining oil at atmospheric pressure, dividing by the amount of crude remaining. It indicates how much gas there is for each barrel of crude, at standard conditions (60°F, 14.7 psi). The API gravity: is a specific gravity scale developed by the American Petroleum Institute (API), to determine the relative density of oil and its derivatives; it's expressed in API degrees, and is inversely proportional to the specific gravity. The Bo compares the volumes of crude and gas dissolved in the oilfield versus the volume of that crude on the surface (at standard conditions).

Based on this information, the different types of crude (Pirson [1]) are classified in:

- i. Black Oil
- ii. Volatile Oil
- iii. Retrograde Oil
- iv. Wet Oil
- v. Dry Gas

In addition to the mentioned properties, the amount of heavy hydrocarbons that contain the crude is decisive (% C7+), also called heavy fraction. In Table 1, the values of the properties for each type of crude are presented [2]. The objective of this paper is to show that if we classify oil crudes taking into account only one property, mistakes can be made, which can lead to serious problems in the design of surface equipment.

Table 1: Oil classification.

Type of Oil	GOR	Bo	°API	% C7+
Black Oil	< 2000	< 2	< 45	> 20
Volatil Oil	2000-8000	> 2	45-60	12-20
Retrograde Gas.	8000-70000	-	> 50	5-12
Wet Gas	60000-100000	-	> 60	< 5
Dry Gas	> 100000	-	-	< 1

Methods

Table 2: Data of wells in the northern area of Argentina.

Oil Fields	Well	GOR	BO	API	C7+
Ramos	R - 1003	7221	1.23	58.6	3.8
	R-1004	6981	1.44	79.7	21
	PL X-1	131	1.3	44	28.03
	PL-16	251	2.18	62	37.45

Palmar	CHO X-1	314	2.17	44	21.32
	PLE X-1	268	2,32	63	35.15
	RL X-1	307	2.33	53	19.87

Information was collected from an oil company, which operates in the Northern area of the Province of Salta and Formosa, from

Table 3: Classification of the crudes based on one property.

Oilfield	Well	Classification by GOR	Classification by °API	Classification by C7+	Classification by Bo
Ramos	R-1003	Volatile	Retrograde	Wet Gas	Black
	R-1004	Volatile	Wet Gas	Black	Black
	PL X-1	Black	Black	Black	Black
	PL-16	Black	Wet Gas	Black	Volatile
Palmar Largo	CHO X-1	Black	Black	Black	Volatile
	PLE X-1	Black	Wet Gas	Black	Volatile
	RL X-1	Black	Retrograde	Volatile	Volatile

Table 4: Classification of the oils studied.

Well	Classification	Observations
R-1003	Volatile	According to the GOR and API, it's a volatile oil, even though its Bo doesn't match the classification.
R-1004	Volatile	IDEM 1003
PL X-1	Black Oil	
PL-16	Volatile	According to GOR and C7+, it would be a Black Oil however, because of the API and BO, it's a volatile oil.
CHO X-1	Volatile	
PLE X-1	Volatile	Behavior similar to that of a volatile oil (high Bo), although the composition is that of a black oil.
RL X-1	Volatile	

Results

The results presented in Table 3, show a classification very contrary to the characteristics of the oils from the north of the province of Salta, which in its majority are Volatile and Retrograde oils. They are even contrary to each other: As seen in Table 3, if the oils are classified considering a single property they give very different results. The correct thing to do is to consider the four properties together to classify the crudes according to the references from Table 1. This new and complete classification is shown in Table 4.

Conclusion

As can be seen when doing the classification of oil it's necessary to have the greatest number of properties to analyze since mistakes can be made, which bring about incorrect decisions in the completion of the well, in the exploitation and in the design of the surface facilities.

the PVT analysis from one of its wells. Table 2 summarizes the relevant data for the classification of crude oil. With this data, the classification of the crudes was done, taking into account one property and then considering all the properties. (Table 3 & 4) show the results of the classification based on the GOR, BO, API and C7+ respectively [3-7].

References

- Pirson S (1965) Ingeniería de yacimientos petrolíferos. Ediciones Omega, Barcelona, Spain.
- Dake LP (1978) Fundamentals of Reservoir Engineering. Elsevier.
- John E (2017) Outlook on oil and gas. Deloitte Center for Energy Solutions.
- Fangming L, Zhongyuan T, Aming J, Xiaoxia W (2009) Prediction of reservoir depletion degree and production GOR using logging-while-drilling data. Petroleum Exploration and Development 36(5): 617-622.
- Liqiang S, Feng W, Jianhai M, Guoqing F, Hang Y (2014) Quantitative calculation of GOR of complex oil-gas-water systems with logging data: A case study of the Yingdong Oil/Gas Field in the Qaidam Basin. Natural Gas Industry B 1(2): 172-177.
- Lee W, Barger W (1996) Gas Reservoir Engineering. SPE 5: 349.
- Schlumberger Sureenco SA (2018) Intelligent completion.



Creative Commons Attribution 4.0
International License

For possible submissions Click Here

[Submit Article](#)



Progress in Petrochemical Science

Benefits of Publishing with us

- High-level peer review and editorial services
- Freely accessible online immediately upon publication
- Authors retain the copyright to their work
- Licensing it under a Creative Commons license
- Visibility through different online platforms